

ACB-EW

Analogue Waterproof Multi Heat Sensor

Features

- ▶ User selectable modes
- ▶ Incorporates Fixed Temperature and Rate Of Rise Heat elements
- ▶ Twin fire LEDs allow 360° viewing
- ▶ Pulsing/non-pulsing controlled from panel*
- ▶ Electronically Addressed
- ▶ IP67 Rated]
- ▶ Supplied with fixing base
- ▶ LPCB & VdS approved to Classes A, B & C.



Description

Model ACB-EW is a Waterproof Multi-Heat Sensor, which is fully compatible with Hochiki's ESP Analogue Addressable Protocol.

The ACB-EW incorporates a variable Fixed Temperature heat element and a Rate Of Rise heat element, both of which are controlled from the Control Panel, allowing either thermal element or both elements simultaneously to be active

in making the fire decision. The sensor polling LED's can also be controlled via the Control Panel (pulsing/non-pulsing).

Rated to IP67, the ACB-EW can be used externally and is supplied with its own fixing base which is used to fix the sensor. Flying leads from the sensor connect directly to the loop via waterproof connectors.

Specification

Ordering Code	ACB-EW
Operating Voltage	17-41 VDC
Low Power Mode	110 µA (typ.)
Quiescent Current	350 µA (typ.)
Alarm Current (controlled by CIE)	9.1mA (excluding remote indicator)
Transmission Method	Digital Communications Using ESP
Operating Temperature Range	-10 °C to +50 °C
Storage Temperature Range	-30 °C to +70 °C
Maximum Humidity	95% RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP67
Colour / Case Material	Ivory/ Polycarbonate
Weight (g)	100
Diameter (mm) / Height (mm)	100 / 46
Compatible Bases	Supplied base only
Base Fixing Centres (mm)	48 ~ 74

*Control Panel compatibility required