

CCP-KS03

Conventional 3-Position Key Switch Manual Call Point

Features

- ▶ 3 position keyswitch
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Other colours available on request.



Description

The CCP-KS03 is an orange Conventional call-point based upon the industry standard KAC world series housing and features easy to install, push-fit wiring terminals.

The unit features a 3-position keyswitch, marked “AUTO”, “BOOST” and “OFF” which can be used for control of other equipment. The unit can support either a ‘Frangible Glass’ element or a ‘Non Frangible Plastic’ element.

Specification

| | | | |
|---------------------------------------|---------------------------------------------------------|--------------|-----------------------------------------|
| Ordering codes | CCP-KS03 | | |
| Nominal operating resistance | 470 Ω | | |
| Maximum contact resistance | 200 Ω | | |
| IP rating | IP24 | | |
| Operating / Storage temperature range | - 10 °C to + 55 °C | | |
| Colour / Case material | Orange / ABS | | |
| Weight (g) / Dimensions (mm) | 110 / W 89 x H 93 x D 27.5 (Flush mount) | | |
| | 161 / W 89 x H 93 x D 59.5 (Surface mount with backbox) | | |
| Accessories | Frangible element | KAC / G / HE | Non-frangible element KAC / EWS / HE |