

Intrinsically Safe Weatherproof Conventional Call Point

CCP-W-IS



Features

- ▶ Sealed to IP67
- ▶ Supports either a 'Frangible' glass element or a 'Non Frangible' plastic element
- ▶ Terminals can accommodate up to a 2.5 mm² solid conductor
- ▶ Approved to EN54 Part 12
- ▶ Rugged design, with anti-tamper facility
- ▶ ATEX Classification to II 1GD Ex ia IIC T4 Ga
- ▶ SIL Level 2 approved variant available

Description

The CCP-W-IS is a conventional weatherproof call point based upon the industry standard KAC world series housing, and which can be used externally in hazardous areas.

Specification	
Ordering Codes	CCP-W-IS
Operating Voltage	15 - 30 V dc
Operating Temperature Range	-25 °C to + 70 °C
Storage Temperature Range	-25 °C to + 70 °C
ATEX Classification	II 1GD Ex ia IIC T4 Ga
Maximum Humidity	93%RH - Non Condensing (at 40 °C)
Ingress Protection Rating	IP67
Colour / Case Material	Red / Polyphenylene Oxide
Weight (g) / Dimensions (mm)	350 / W97.5 x H93 x D71

HOCHIKI

World Class Leaders in Fire Detection Since 1918